

# Leica RTC360 3D Reality Capture Solution

Fast. Agile. Precise.



## Fast

The Leica RTC360 laser scanner makes 3D reality capture faster than ever before. With a measuring rate of up to 2 million points per second and advanced HDR imaging system, the creation of colored 3D point clouds can be completed in under 2 minutes. Plus, automated targetless field registration (based on VIS technology) and the seamless, automated transfer of data from site to office reduce time spent in the field and further maximize productivity.



## Agile

Small and lightweight, the Leica RTC360 scanner's portable design and collapsible tripod mean it's compact enough to fit into most backpacks, ready to be taken anywhere. Once on-site, easy-to-use one-button operation makes for fast, hassle-free scanning.



## Precise

Low noise data allows for better images, resulting in crisp, high-quality scans that are rich in detail and ready for use in a range of applications. Combined with Cyclone FIELD 360 software for automated registration in the field, the Leica RTC360 scanner offers outstanding precision that can be checked on-site.



**RPG Squarefoot Solutions**

(800) 521-6319

[www.rpg.com](http://www.rpg.com)

[info@rpg.com](mailto:info@rpg.com)



# Leica RTC360 Product Specifications

## GENERAL

3D Laser Scanner	High-speed 3D laser scanner with integrated HDR spherical imaging system and Visual Inertial System (VIS) for real time registration
------------------	--

## PERFORMANCE

Data acquisition	< 2 min for complete full dome scan and spherical HDR image at 6mm @ 10m resolution
Real time registration	Automatic point cloud alignment based on real time tracking of scanner movement between setups based on Visual Inertial System (VIS) by video-enhanced inertial measurement unit
Double scan	Automatic removal of moving objects

## SCANNING

Distance measurement	High-speed, high dynamic time of flight enhanced by Waveform Digitizing (WFD) technology
Laser Class	1 (in accordance with IEC 60825-1:2014), 1550nm (invisible)
Field of view	360° (horizontal) / 300° (vertical)
Range	Min. 0.5 - up to 130 m
Speed	Up to 2'000'000 pts / sec
Resolution	3 user selectable settings (3/6/12mm @ 10m)
Accuracy*	Angular accuracy 18" Range accuracy 1.0 mm + 10 ppm 3D point accuracy 1.9 mm @ 10 m 2.9 mm @ 20 m 5.3 mm @ 40 m
Range noise**	0.4 mm @ 10 m, 0.5 mm @ 20 m

## IMAGING

Camera	36 MP 3-camera system captures 432 MPx raw data for calibrated 360° x 300° spherical image
Speed	1 minute for full spherical HDR image at any light condition
HDR	Automatic, 5 brackets

## NAVIGATION SENSORS

Visual Inertial System	Video enhanced inertial measuring system to track movement of the scanner position relative to the previous setup in real time
Tilt	IMU based, Accuracy: 3' for any tilt
Additional sensors	Altimeter, Compass, GNSS

## OPERATION

On scanner	Touch-screen control with finger touch, full color WVGA graphic display 480 x 800 pixels
Mobile devices	Leica Cyclone FIELD 360 app for iPad or Android tablets including: - Remote control of scan functions - 2D & 3D data viewing - Tagging - Automatic alignment of scans
Wireless	Integrated wireless LAN (802.11 b/g/n)
Data storage	Leica MS256, 256GB exchangeable USB 3.0 flash drive

## DESIGN & PHYSICAL

Housing	Aluminium frame and sidecovers
Dimensions	120mm x 240mm x 230mm / 4.7" x 9.4" x 9.1"
Weight	5.35 kg / 11.7 lbs, nominal (w/o batteries)
Mounting mechanism	Quick mounting on 5/8" stub on lightweight tripod / optional tribrach adapter / survey tribrach adapter available

## POWER

Internal battery	2 x Leica GEB361 internal, rechargeable Li-Ion batteries. Duration: Typically up to 4 hours Weight: 340 g per battery
External	Leica GEV282 AC adapter

## ENVIRONMENTAL

Operating temperature	-5° to +40° C
Storage temperature	-40° to +70° C
Dust/Humidity***	Solid particle/liquid ingress protection IP54 (IEC 60529)



Leica Cyclone FIELD 360



Leica Cyclone REGISTER 360



Leica ScanStation P50

**active** >>  
Customer Care

### Your Trusted Active Customer Care

Active Customer Care is a true partnership between Leica Geosystems and its customers. Customer Care Packages (CCPs) ensure optimally maintained equipment and the most up-to-date software to deliver the best results for your business. The myWorld @ Leica Geosystems customer portal provides a wealth of information 24/7.

All specifications are subject to change without notice.

All accuracy specifications are on a level of confidence of 68% according to the Guide of the Expression of Uncertainty in Measurement (JCGM100:2008) unless otherwise noted.

\* At 89% albedo.

\*\* For single shot measurements

\*\*\* For upright and upside down setups with a +/- 15° inclination

Scanner: Laser class 1 in accordance with IEC60825:2014

iPhone and iPad are trademarks of Apple Inc.

Android is a trademark of Google.



**RPG Squarefoot Solutions**

(800) 521-6319

[www.rpg.com](http://www.rpg.com)

[info@rpg.com](mailto:info@rpg.com)

