HP DesignJet T2600 Multifunction Printer series



Engineered for collaboration – Turn your workgroups into highly efficient teams



Seamless experience – Designed for all

- Radically simple experience with a smart 396.2 mm (15.6 in) interface and the easiest PDF printing with HP Click.
- Engage in a collaborative workstyle with teams quickly accessing shared folders to print and
- Empower your workforce. Easily print and share jobs from the cloud with your mobile device and HP Smart app
- Fits your workplace with the most compact footprint and most quiet operation, with up to 87% less noise.3

Unleash performance – To turn design into delivery

- Showcase design versatility from precise line drafts to boldly coloured 3D renders, with HP Bright Office Inks.
- Provide the highest accuracy and display the finest details with the unique Adobe PDF Print
- Meet deadlines with the fastest speed up to 180 D/hr, the only automatic print stacking³, and dual rolls.5
- · Easily digitise your projects with automated scanning, user-centric quicksets, and postediting capabilities.

Secure – World's most secure large-format printer6

- Rely on the best network protection with features like HP Secure Boot and whitelisting. 6
- Control who accesses the printer and its confidential documents with secure user authentication.
- Keep your fleet secure at any time with HP JetAdvantage Security Manager.

For more information, please visit http://www.hp.com/go/designjett2600



RPG Squarefoot Solutions (800) 521-6319 www.rpg.com info@rpg.com

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: http://www.hp.com/go/learnaboutsupplies

¹ Compared to Canon Direct Print & Share and based on "One Click Print." Once image is selected, one-click printing when printing the entire file without any modifications to the print settings. Applicable to PDF, JPEG, TIFF, DWF, HP-GL/2 files.

² Using Lightweight Directory Access Protocol (LDAP).

³ Based on comparable large-format inkjet printers under €12,000 as of December, 2018. IDC figures show that Canon, Epson, and HP combine for 98% share of this printing category worldwide as of Q3, 2018. Most compact footprint calculated using all devices in "Operation mode" with an Open Basket and the arm of the Screen (front panel) spread out to enable user interaction and the scanner lifted on the Canon TX 3000 T36 MFP and the Epson SC-T5200 MFP to enable top media loading. Most quiet according to internal HP testing of sound pressure level during operating mode (plain paper, line drawing, Normal mode) compared to published specification of competitive printers. Percentage calculations of noise based on lineal units vs. Canon TX-3000 published spec of 51dB(A). Fastest print speed based on sustained printing speeds. Only automatic print

^{**}Stacking based on unicity of the integrated stacker versus competitive printers only offering basket or bin with stacking position.

*Requires purchase of the HP DesignJet TZ600 PostScript® models or optional HP DesignJet PostScript/PDF Upgrade Kit. Highest accuracy and finest details compared to printers without the embedded Adobe technology excluding RIP users, and based on internal HP testing with PDF files containing special fonts, PANTONE® colors, smooth shading, overprint, and transparencies that can only be reproduced using the Adobe PDF Print Engine. The Adobe PDF Print Engine (APPE) is Adobe's high speed, high fidelity print platform. To learn more, visit http://www.adobe.com/products/pdfprintengine.

*Dual rolls included with HP DesignJet TZ600dr multifunction printers only.

⁶ Advanced embedded security features are based on HP review of 2019 published embedded security features of competitive printers, as of February 2019.

Technical specifications

/hr, 19.3 sec/A1 ¹ 400 x 1200 optimised dpi rmal Inkjet x 3 x 3 x 3 mm () 3 x 22 x 3 x 3
rmal Inkjet x3 x3 x3 mm 0 3 x22 x3 x3 mm 0 3 x22 x3 x3 mm 0 5 sed (C, M, Y, PK, G); pigment-based (mK) rsal printhead m (PDF addressable at 1200 dpi); pto 7.62 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) pto 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) pto 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) colo dpi colo mm (JPEG); 610 x 15,000 mm (TIFF); 914 x 8000 mm (PDF) [®] ; m; IFF and multipage TIFF, PDF and multipage PDF [®] hared network folder, printer HDD, email eed, automatic front-loading roll feed, smart roll switching ³ , integrated output stacker, media bin, automatic tral cutter rs: traight-through scan paper path for sheet and cardboard originals 279 to 914 x 1219 mm 914 mm A2, A1, A0 (A, B, C, D, E) 28 g/m² 1.5 mm (Up to 19.7 mil) awings: Maps; Orthophotos; Presentations; Renderings 8 (file processing) ⁴ ; 8 self-encrypting Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TFTP nI)), SNMP (v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), IPsecemial), Raw IP printing (9100), UP, IP; P8 y print, INT IM v2, SMBV3, SSLT, SAB 2.13 x authentication (LEAP)
x 3 x 3 x 3 mm 0 3 x 22 x 3 x 3 mm 0 3 x 22 x 3 x 3 mm 0 3 x 22 x 3 x 3 mm 0 3 x 22 x 3 x 3 mm 0 3 x 22 x 3 x 3 mm 0 great (C, M, Y, PK, G); pigment-based (mK) great printhead great (C, M, Y, PK, G); pigment-based (mK) great printhead great (C, M, Y, PK, G); pigment-based (mK) great printhead great (x, Y,
3 x 22 x 3 x 3 mm () sed (C, M, Y, pK, G); pigment-based (mK) rsal printhead 2 m (PDF addressable at 1200 dpi); pto 7.62 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) pto 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) pto 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) pto 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) pto 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) pto 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) pto 15.24 cm/sec (grayscale, 200 dpi) pto
seed (C, M, Y, pK, G); pigment-based (mK) rsal printhead m (PDF addressable at 1200 dpi); m (PDF addressable at 1200 dpi); m (PDF addressable at 1200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) pto 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) 100 dpi 100 0 mm (JPEG); 610 x 15,000 mm (TIFF); 914 x 8000 mm (PDF) [®] ; 7: TIFF and multipage TIFF, PDF and multipage PDF [®] 101 and nuttipage TIFF, PDF and multipage PDF [®] 102 and network folder, printer HDD, email 103 and page and page page page page page page page page
rsal printhead Image: PDF addressable at 1200 dpi); Ip to 7.62 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) lp to 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) lp to 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) lp to 15.24 cm/sec (color, 200 dpi) lp to 15.24 cm/sec (grayscale, 200 dpi) lp lp to 15.24 cm/sec (grayscale, 200 dpi) lp lp lp to 15.24 cm/sec (grayscale, 200 dpi) lp lp lp lp to 15.24 cm/sec (grayscale, 200 dpi) lp
m (PDF addressable at 1200 dpi); m (PDF addressable at 1200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) lp to 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) lp to 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) loo dpi loo loo dpi loo loo dpi loo loo loo loo loo loo loo loo loo lo
m (PDF addressable at 1200 dpi); Ip to 7.62 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) Ip to 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) Ip to 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) Ip to 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) Ip to 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) Ip to 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) Ip to 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) Ip to 15.24 cm/sec (grayscale, 200 dpi) I
Ip to 7.62 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) Ip to 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) Ip to 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) Ip to 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) Ip to 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) Ip to 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) Ip to 15.24 cm/sec (grayscale, 200 dpi) Ip to 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) Ip to 15.24 cm/sec (grayscale, 200
ip to 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) 100 dpi 100 dpi 100 mm (JPEG); 610 x 15,000 mm (TIFF); 914 x 8000 mm (PDF) [®] ; 11. 11. 11. 11. 11. 11. 11. 1
ip to 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi) 100 dpi 100 dpi 100 mm (JPEG); 610 x 15,000 mm (TIFF); 914 x 8000 mm (PDF) [®] ; 11. 11. 11. 11. 11. 11. 11. 1
3000 mm (JPEG); 610 x 15,000 mm (TIFF); 914 x 8000 mm (PDF) ^B ; n; IFF and multipage TIFF, PDF and multipage PDF ^B hared network folder, printer HDD, email eed, automatic front-loading roll feed, smart roll switching ³ , integrated output stacker, media bin, automatic tral cutter rs: straight-through scan paper path for sheet and cardboard originals 279 to 914 x 1219 mm 914 mm A2, A1, A0 (A, B, C, D, E) 28 g/m² 1.5 mm (Up to 19.7 mil) awings: Maps; Orthophotos; Presentations; Renderings 16 (file processing) ⁴ ; 18 self-encrypting Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TFTP nily), SNMP (v1, v2c, v3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP, HTTPS), IPsecemail), Raw IP printing (9100), LPD, IPP, W5 print, NTLM v2, K9, SMBV3, SSL/TLS, 802.11 x authentication (LEAP)
n; IFF and multipage TIFF, PDF and multipage PDF ^B hared network folder, printer HDD, email eed, automatic front-loading roll feed, smart roll switching ³ , integrated output stacker, media bin, automatic tral cutter rs: straight-through scan paper path for sheet and cardboard originals 279 to 914 x 1219 mm 914 mm A2, A1, A0 (A, B, C, D, E) 28 g/m² 1.5 mm (Up to 19.7 mil) awings: Maps; Orthophotos; Presentations; Renderings 16 (file processing) ⁴ ; 18 self-encrypting Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TFTP nly), SNMP (v1, v2c, v3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP, HTTPS), IPsee mail), Raw IP printing (9100), LPD, IPP, W5 print, NTLM v2, K9MBV3, SSL/TLS, 802.118 authentication (LEAP)
IFF and multipage TIFF, PDF and multipage PDF ⁸ hared network folder, printer HDD, email eed, automatic front-loading roll feed, smart roll switching ³ , integrated output stacker, media bin, automatic tral cutter restraight-through scan paper path for sheet and cardboard originals 279 to 914 x 1219 mm 914 mm A2, A1, A0 (A, B, C, D, E) 28 g/m² 1.5 mm (Up to 19.7 mil) awings; Maps; Orthophotos; Presentations; Renderings 8 (file processing) ⁴ ; 8 self-encrypting Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TFTP nly), SNMP (v1, v2c, v3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP, HTTPS), IPsee mail), Raw IPp rinting (91000), LPD, IPP, W5 print, NTLM v2, SMBV3, SSL/TLS, 802.11 xuthernication (LEAP,
eed, automatic front-loading roll feed, smart roll switching ³ , integrated output stacker, media bin, automatic roll actuter restraight-through scan paper path for sheet and cardboard originals restraight-through scan paper path for sheet and cardboard originals restraight-through scan paper path for sheet and cardboard originals restraight mm 914 mm A2, A1, A0 (A, B, C, D, E) 28 g/m² 1.5 mm (Up to 19.7 mil) awings; Maps; Orthophotos; Presentations; Renderings 8 (file processing) ⁴ ; 8 self-encrypting Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TFTP rily), SNMP (v1, v2c, v3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP, HTTPS), IPsee email), Raw IP printing (9100), LPD, IPP, W5 print, NTLM v2, K9MBV3, SSL/TLS, 802.118 authentication (LEAP)
eed, automatic front-loading roll feed, smart roll switching ³ , integrated output stacker, media bin, automatic trial cutter "rs:traight-through scan paper path for sheet and cardboard originals 279 to 914 x 1219 mm 914 mm A2, A1, A0 (A, B, C, D, E) 28 g/m² 1.5 mm (Up to 19.7 mil) awings; Maps; Orthophotos; Presentations; Renderings 0 (file processing) ⁴ ; 0 self-encrypting Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TFTP nly), SNMP (v1, v2c, v3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP, HTTPS), IPsee
thal cutter "straight-through scan paper path for sheet and cardboard originals 279 to 914 x 1219 mm 914 mm A2, A1, A0 (A, B, C, D, E) 28 g/m² 1.5 mm (Up to 19.7 mil) awings; Maps; Orthophotos; Presentations; Renderings 16 (file processing) ⁴ ; 18 self-encrypting Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TFTP nly), SNMP (v1, v2c, v3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP, HTTPS), IPsee mail), Raw IP printing (91000), LPD, IPP, W5 print, NTLM v2, SMBV3, SSL/TLS, 802.118 authentication (LEAP)
thal cutter "straight-through scan paper path for sheet and cardboard originals 279 to 914 x 1219 mm 914 mm A2, A1, A0 (A, B, C, D, E) 28 g/m² 1.5 mm (Up to 19.7 mil) awings; Maps; Orthophotos; Presentations; Renderings 16 (file processing) ⁴ ; 18 self-encrypting Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TFTP nly), SNMP (v1, v2c, v3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP, HTTPS), IPsee mail), Raw IP printing (91000), LPD, IPP, W5 print, NTLM v2, SMBV3, SSL/TLS, 802.118 authentication (LEAP)
thal cutter "straight-through scan paper path for sheet and cardboard originals 279 to 914 x 1219 mm 914 mm A2, A1, A0 (A, B, C, D, E) 28 g/m² 1.5 mm (Up to 19.7 mil) awings; Maps; Orthophotos; Presentations; Renderings 16 (file processing) ⁴ ; 18 self-encrypting Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TFTP nly), SNMP (v1, v2c, v3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP, HTTPS), IPsee mail), Raw IP printing (91000), LPD, IPP, W5 print, NTLM v2, SMBV3, SSL/TLS, 802.118 authentication (LEAP)
279 to 914 x 1219 mm 914 mm A2, A1, A0 (A, B, C, D, E) 28 g/m² 1.5 mm (Up to 19.7 mil) awings; Maps; Orthophotos; Presentations; Renderings 8 (file processing) ⁴ ; 8 self-encrypting Ethernet (1 000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TFTP nly), SNMP (v1, v2c, v3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP, HTTPS), IPsee mail), Raw IP printing (91000), LPD, IPP, W5 print, NTLM v2, SMBV3, SSLT/LTS, 802.118 authentication (LEAP,
914 mm A2, A1, A0 (A, B, C, D, E) 28 g/m² 1.5 mm (Up to 19.7 mil) awings: Maps; Orthophotos; Presentations; Renderings 1 (file processing) ⁴ ; 3 self-encrypting Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TFTP nly), SNMP (v1, v2c, v3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP, HTTPS), IPsee mail), Raw IP printing (9100), LPD, IPP, W5 print, NTLM v2, SMBV3, SSLT/LTS, 802.118 authentication (LEAP)
A2, A1, A0 (A, B, C, D, E) 28 g/m² 1.5 mm (Up to 19.7 mil) awings; Maps; Orthophotos; Presentations; Renderings 16 (file processing) ⁴ ; 3 self-encrypting Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TFTP nly), SNMP (v1, v2c, v3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP, HTTPS), IPsee mail), Raw IP printing (9100), LPD, IPP, W5 print, NTLM v2, SMBv3, SSLTLS, 802.1X suthentication (LEAP,
28 g/m² 1.5 mm (Up to 19.7 mil) awings; Maps; Orthophotos; Presentations; Renderings 1 (file processing) ⁴ ; 3 self-encrypting Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TFTP nly), SNMP (v1, v2c, v3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP, HTTPS), IPsecemail), Raw IP printing (9100), LPD, IPP, W5 print, NTLM v2, SMBV3, SSL/TLS, 802.118 authentication (LEAP)
1.5 mm (Up to 19.7 mil) awings; Maps; Orthophotos; Presentations; Renderings (file processing) ⁴ ; 3 self-encrypting Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TFTP nly), SNMP (v1, v2c, v3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP, HTTPS), IPsec mail), Raw IP printing (9100), LPD, IPP, W5 print, NTLM v2, SMBv3, SSL/TLS, 802.1 X8 utherhotication (LEAP,
awings; Maps; Orthophotos; Presentations; Renderings (file processing) ⁴ ; 8 self-encrypting Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TFTP nly), SNMP (v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), IPsecemail), Raw IP printing (9100), LPD, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (LEAP,
3 (file processing) ⁴ ; 3 self-encrypting Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TFTP nly), SNMP (v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), IPsec email), Raw IP printing (9100), LPD, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (LEAP,
is self-encrypting Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TFTP nly), SNMP (v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), IPsec email), Raw IP printing (9100), LPD, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (LEAP,
Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TFTP nly), SNMP (v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), IPsec email), Raw IP printing (9100), LPD, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (LEAP,
nly), SNMP (v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), IPsec email), Raw IP printing (9100), LPD, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (LEAP,
nly), SNMP (v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), IPsec email), Raw IP printing (9100), LPD, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (LEAP,
ript Printer: Adobe PostScript 3, Adobe PDF 1.7, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4; Non-PostScript Printer /2, HP-RTL, TIFF, JPEG, CALS G4
ostScript Printer: Adobe PostScript 3, Adobe PDF 1.7
orinting from USB flash drive, print from network shared folder, email printing, HP driver for Windows, HP Print • for Android, Apple AirPrint driver for MacOS and for iOS, HP Print for Chrome OS, HP Click, HP Smart App for iC
droid ript Printer: Raster, PostScript and PDF drivers for Windows, AirPrint for macOS; Non-PostScript Printer: Raster
for Windows, AirPrint for macOS
ure Boot, Whitelisting, TPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPv3, HTTPS, -IPP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP antage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypting ncrypted PIN printing, Syslog security logging
.760 x 1240 mm
7.767 x 800 mm
707 X 000 111111
roll: 106 kg, dual-roll: 109 kg
roll: 137 kg, dual-roll: 142 kg
ignJet T2600 Multifuntion Printer, printer stand and media bin, 39.62 cm (15.6 in) touchscreen, spindle(s) ⁵ , ads, introductory ink cartridges, user guide, power cords
k, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP antage Security Manager, HP SmartTracker (optional)
⁹ C
0% RH
55°C
A) (aparation), 33 dD(A) (idla), x 17 dD(A) (class)
A) (operating); 32 dB(A) (idle); < 17 dB(A) (sleep)
(A) (operating); ≤ 4.9 B(A) (idle); ≤ 3.5 B(A) (sleep)
(printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off)
oltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max
o and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA)
ant with Class A requirements, including: EU (EMC Directive)
Y STAR, ErP, WEEE, RoHS (EU), REACH, EPEAT
ear limited hardware warranty











Product

3EK15A	HP DesignJet T2600dr 36-in PostScript Multifunction Printer
3XB78A	HP DesignJet T2600 36-in PostScript Multifunction Printer

Accessories

HP DesignJet PostScript/PDF Upgrade Kit CN538A HP DesignJet 3-in Core Adapter HP DesignJet 36-in Spindle N7P47AA HP USB 3.0 to Gigabit LAN Adapter

Original HP printing supplies

B3P06A	HP 727 DesignJet Printhead	
P2V62A	HP 730 130-ml Cyan DesignJet Ink Cartridge	
P2V63A	HP 730 130-ml Magenta DesignJet Ink Cartridge	
P2V64A	HP 730 130-ml Yellow DesignJet Ink Cartridge	
P2V65A	HP 730 130-ml Matte Black DesignJet Ink Cartridge	
P2V66A	HP 730 130-ml Gray DesignJet Ink Cartridge	
P2V67A	HP 730 130-ml Photo Black DesignJet Ink Cartridge	
P2V68A	HP 730 300-ml Cyan DesignJet Ink Cartridge	
P2V69A	HP 730 300-ml Magenta DesignJet Ink Cartridge	
P2V70A	HP 730 300-ml Yellow DesignJet Ink Cartridge	
P2V71A	HP 730 300-ml Matte Black DesignJet Ink Cartridge	
P2V72A	HP 730 300-ml Gray DesignJet Ink Cartridge	
P2V73A	HP 730 300-ml Photo Black Design let Ink Cartridge	

Use Original HP inks and printheads, and HP large format printing materials, to Use Uriginal HP inks and printneads, and HP large format printing materials, to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system, and Original HP inks are designed to maximize the life o HP printheads. Protect your HP printer investment by using Original HP inks for full HP warranty protection. For more information, visit hp.com/go/OriginalHPinks.

Original HP large format printing materials

C6810A HP Bright White Inkjet Paper (FSC® certified)⁶ (recyclable)⁷ 914 mm x 91.4 m

C6980A HP Coated Paper (PEFC™ certified)⁶ (recyclable)⁷ 914 mm x 91.4 m (36 in x

LEC80A HP Universal Heavyweight Coated Paper, 3-in Core (FSC® certified)⁶ (recyclable)⁷ 914 mm x 91.4 m (36 in x 300 ft)

D9R28A HP Everyday Matte Polypropylene, 3-in Core 914 mm x 61 m (36 in x 200 ft)

UB9P6E HP 3 year Next Business Day Onsite Hardware Support with Defective Media

UBBU4E IP 3 year Next Business Day Onsite Hardware Support with Defective Media Retention (2-roll)
UBBP7E IP 4 year Next Business Day Onsite Hardware Support with Defective Media Retention (1-roll)

UBBUSE HP 4 year Next Business Day Onsite Hardware Support with Defective Media Retention (2-roll) **UB9P8E** HP 5 year Next Business Day Onsite Hardware Support with Defective Media

on (1-roll)

Retention (1-roll)

UBBUGE HP 5 year Next Business Day Onsite Hardware Support with Defective Media Retention (2-roll)

UBBOPPE HP 1 year Post Warranty Next Business Day Onsite Hardware Support with Defective Media Retention (1-roll)

UBBUTPE HP 1 year Post Warranty Next Business Day Onsite Hardware Support with Defective Media Retention (2-roll)

UTXME HP Preventive Maintenance Service

H451BE HP Installation Service with Network Setup

HP Design, Jet Support Services offer installation, maintenance, and extended support services (e.g. 2,3,4 and 5 years). For more information, please visit hp.com/go/cpc

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

ECO highlights

- Save paper with automatic print settings and image nesting ENERGY STAR® certified ¹ and EPEAT® registered² Free, convenient HP ink cartridge recycling ³ FSC®.certified papers ⁵, recyclable HP media; some HP media eligible for takeback program⁵

Please recycle large-format printing hardware and printing supplies. Find out how at

¹ ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the

¹ ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency.

² EPEAT® registered where applicable. EPEAT registration varies by country. See http://www.peeat.net for registration status by country.

³ Program availability varies. Please check http://www.hp.com/recycle for details.

⁴ BMG trademark license code FSC®-Clot15319, see http://www.fsc.org. HP trademark license code FSC®-Clot7543, see http://www.fsc.org. Not all FSC®-certified products are available in all regions. For information about HP large format printing materials, please wish http://www.HPLFMedia.com.

⁵ Recyclable HP papers can be recycled through commonly available recycling programs, or according to region-specific practices. Some HP media are eligible for return through the HP Large Format Media take-back program. Programs may not exist in your area. See http://www.HPLFMedia.com/hp/ecosolutions for details.

¹ Mechanical printing time. Printed in Fast mode with Economode on, using HP Bright

¹ Mechanical printing time. Printed in Fast mode with Economode on, using HP Bright White Inkjet Paper (bond) and Original HP links.
² ±0.1% of the specified vector length or ±0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E HP Matte Film in Best or Normal mode with Original HP links
³ Applicable for dual-roll printers only.

⁴ Based on 8 GB RAM. ⁵ Single-roll printers come with one spindle, dual-roll printers come with two

Single-tot printers come with one spinule, dual-tot printers come with two spinules.

6 BMG trademark license code FSC®-C115319, see http://www.fsc.org. HP trademark license code FSC®-C017543, see http://www.pfc.org. HP trademark license code PEFC™/29-31-261, see http://www.pfc.org. HP trademark license code PEFC™/29-31-198, see http://www.pfc.org. Not all FSC®- or PEFC™-certified products are available in all registers. available in all regions.

Can be recycled through commonly available recycling programs.

8 Applicable for PostScript printers only









